



In 1982, Reitnouer introduced the first totally bolted aluminum flatbed trailer—an innovation that challenged the mindset of an entire industry. Today, Reitnouer is the design of choice. While our basic philosophy hasn't changed, our products are continually evolving to meet your changing needs. We offer our MaxMiser model—a 90,000 lb. GVWR* heavyweight designed to meet most customers' everyday needs. If the MaxMiser isn't big enough, Reitnouer offers the Big Bubba—a 100,000 lb. GVWR model that continues to set the standard for heavyweights since its introduction in 1992. Big Bubba combines the superior strength for which Reitnouer is famous, with innovative weight-saving features. The Big Bubba still weighs thousands less than any steel trailer even approaching Big Bubba's hauling capacity. Need even more capacity? The Bigger Bubba is your ideal choice—a 110,000 lb. GVWR monster with bigger bones to handle the most outrageous jobs. And for our weightwatching customers who want high strength but don't haul heavy concentrated loads, we have the MaxLite model—an 80,000 lb. GVWR model designed to maximize payload.

*GVWR = GROSS VEHICLE WEIGHT RATING

REPAIRS: A major concern of our customers is the maintenance and repairs of their trailers.

Nearly every aluminum component is precision punched for easy and inexpensive replacement.

Accidents will happen. Fortunately, the advanced engineering and attention to detail that makes a Reitnouer trailer strong, durable, and reliable also makes it inexpensive to maintain and repair.

















Reitnouer trailers boast many exclusive innovations. But what really makes our trailers stand out is that every Reitnouer aluminum trailer is bolted. With the exception of the rub rail, there's not a welded aluminum joint anywhere on a Reitnouer. Research and experience shows that when a heat treated aluminum alloy is welded, the intense heat required to weld the joint significantly reduces the aluminum's tensile strength. As a result, bolting makes Reitnouer flatbed trailers stronger and more durable.

Engineered for long life, Reitnouer trailers have a rock-solid design proven over millions of miles. Reitnouer continues to revolutionize the industry and maintain its standards by which all other trailers are measured. Reitnouer will uphold its tradition of leadership and innovation to continue providing our customers with stronger, lighter trailers.



Optional four wood nailers or four wood nailers with a center tie-down track is the setup for hauling coils or other loads where additional wood or tie-downs are needed.

Three-piece floating outriggers minimize the stress on the main beams.

Suspension hanger boxes are boxed in from side-to-side to minimize the stresses that are transferred to the main rails.





Two-piece load levelers for drop decks offer lighter weight handling and placement anywhere along the trailer deck. Snap-in pockets offer superior strength in the pocket-to-side-rail connection.

Optional log pockets enable use of heavy duty stakes to secure logs. The number of pockets and pocket locations can be tailored to customer specifications. An innovative snap-in floor enables the floor to become part of the main beam.

In addition, the extruded inner flange allows cross member stress to be distributed over a much larger area.

Solid one-piece cross members are designed with an offset web and a unique, reinforced inner extrusion that adds reinforcement between the main beams.





STANDARD SPECIFICATIONS

Main Rail:	Two-piece extruded and bolted; 4" camber; 26" deep in center; 6061 T6		
Cross members:	One-piece 5" double reinforced modified "C" channel on 15" centers (12" optional); bolted; 6061		
Floor:	1-3/8" aluminum, heavy duty safety tread, interlocked, with three apitong nailers;		
	optional four wood nailers; custom floor designs also available		
Side Rail Assembly:	1-5/8" x 3-1/2" pockets on 2' centers with spool spacers between pockets,		
	3/8" x 2-1/2" deep rub rail; DOT tape		
Outriggers:	Three-piece floating		
Deck Dimensions:	Drop Deck Only—Front Deck-10' 8"; Rear Deck-depends upon overall length;		
	Drop-23"; Rear Height-40"; other lengths and King Pin settings available.		
Axles:	5" Round; P Spindle Ends		
Brakes:	16-1/2" x 7" extended service brakes, quick change with parking brakes; 8-5/8" optional;		
	4S/2M antilock brakes		

Suspension:	Hendrickson Intraax®; others available		
Landing Gear:	Binkley 51,000; crossbracing tied to four cross members; Holland & Jost optional		
Upper Coupler:	1/4" hi-tensile steel; powder coated, various settings available		
Electrical/Lights:	Peterson LED lights, hard-wired, modular wiring harness with all Packard connections		
Bumpers:	DOT bumper; 6 rubber dock bumpers; extruded rear corners		
Bolts:	316 Stainless Steel		
Finish:	Natural aluminum; all steel parts primed and finished in color of your choice;		
	suspension and fifth wheel plate are powder coated		
Length:	Available in overall lengths through 53'; widths of 96" or 102"		
Options:	Most industry requested options are available.		
Warranty:	5-year limited		

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. REITNOUER INC. RESERVES THE RIGHT TO SUBSTITUTE COMPONENTS WITHOUT NOTICE UNLESS SPECIFIED ON ORDER.

LOAD RATINGS - MAIN BEAMS ONLY

MaxLite:	40,000 lbs. in 4'	50,000 lbs. in 10'	80,000 lbs. evenly distributed
MaxMiser:	50,000 lbs. in 4'	60,000 lbs. in 10'	90,000 lbs. evenly distributed

Big Bubba:	60,000 lbs. in 4'	70,000 lbs. in 10'	100,000 lbs. evenly distributed
Bigger Bubba:	72,000 lbs. in 4'	85,000 lbs. in 10'	110,000 lbs. evenly distributed





Reitnouer

ALUMINUM TRAILERS

www.reitnouer-trailers.com

4001 Reading Crest Avenue PO Box 13069 Reading, PA 19612 Tel: 610.929.4856

Fax: 610.929.5039

MOVING HEAVEN AND EARTH AND EVERYTHING IN BETWEEN.

DISTRIBUTED BY: